


	Imperial	Metric
Overall Length (Pin Bottom Conn.) <sup>1</sup>	14.28 in	362.7 mm
Overall Length (Box Bottom Conn.) <sup>1</sup>	14.53 in	369.1 mm
Maximum Tool Body Diameter	2.130 in	54 mm
Wash Head Nominal Diameter <sup>2</sup>	2.600 in	66 mm
Maximum Temperature <sup>3</sup>	482°F	250°C
Maximum On-Bottom Bearing Load <sup>4</sup>	9600 lbf	4270 daN
Maximum Off-Bottom Bearing Load <sup>4</sup>	9600 lbf	4270 daN
Maximum Overpull <sup>5</sup>	22600 lbf	10053 daN
Maximum Wash Head Total Flow Area	0.48 in <sup>2</sup>	310 mm <sup>2</sup>
Minimum Wash Head Total Flow Area	0.17 in <sup>2</sup>	110 mm <sup>2</sup>
Recommended Total Flow Area	0.45 in <sup>2</sup>	293 mm <sup>2</sup>
Minimum Internal Port Size <sup>6</sup>	0.14 in <sup>2</sup>	3.6 mm <sup>2</sup>
Burst Pressure	12810 psi	88.3 MPa
Collapse Pressure	12360 psi	85.2 MPa
Peak Power <sup>7</sup>	0.6 HP	0.4 kW
Top Connection	1.500 API REG Box	
Optional Bottom Connection <sup>2</sup>	1.500 API REG Pin or Box	



Operational specifications are for reference only. Actual tool performance may vary depending on a variety of downhole conditions. Performance data is subject to change without notice.

	Imperial	Metric
Maximum Wash Head Port Config	1 x Ø0.44 in, 12 x Ø0.19 in	1 x Ø11.1 mm, 12 x Ø4.8 mm
Minimum Wash Head Port Config	6 x Ø0.19 in	6 x Ø4.8 mm



Box-down & Pin-down options available.

Check back to our website periodically, and follow us on social media.

